

Industrial Waste Application Supplement - No 1



Automotive Services, Mechanical Repairs, Wash Bays, Car Washes

This is an attachment to the Industrial Waste Application. Please provide the following information about your business operations (or intended operations.) This will help us verify appropriate waste treatment and charging.

Business trading name _____

1. Will you be cleaning parts using solvents or degreasers?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
2. Will you have a self-contained parts cleaning unit? If yes , what arrangements will be in place to dispose of the waste?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
	Tankered off site <input type="checkbox"/>	
	Processed on site <input type="checkbox"/>	
3. Will you have a washdown area? If yes , what area is under cover? What area is not under cover? Will you be sharing the washdown area with other businesses?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
	_____ square metres	
	_____ square metres	
	Yes <input type="checkbox"/>	No <input type="checkbox"/>
4. Do you intend to install or have an oil water separator? If yes , what type is it? Capacity Flow rate Do you have a maintenance contract? See note 4 below.	Yes <input type="checkbox"/>	No <input type="checkbox"/>
	Make: _____	
	Model: _____	
	_____ litres, or	
	_____ litres / hour	
	Yes <input type="checkbox"/>	No <input type="checkbox"/>
5. What types of car washing facilities do you intend to have or are currently operating? Note: You can have any combination of car wash types at your premises eg Rollover & Bays. See Car Washes IW PUB32 Information Brochure for explanation of car wash types.	<input type="checkbox"/>	Conveyor
	<input type="checkbox"/>	Roll Over
	<input type="checkbox"/>	Touchless
	<input type="checkbox"/>	Bays

Important Notes

1. All arrestors and washdown design details must be shown on plumbing plans attached to the Application.
2. Triple interceptor traps are not to be used for the pretreatment of fueling area waste and /or wash down bays.
3. Glycol from motor vehicle radiators is a prohibited discharge to sewer and must be stored and transported off site by a licensed liquid waste contractor.
4. You are required to submit a copy of the written maintenance contract to Water Corporation.